


WHAT'S INSIDE


- 1 Front Panel
- 2 Back Panel
- 3 Operating Specifications
- 4 Dimensions & Weight
- 5 Regulatory
- 6 Warranty
- 7 Model Options

FRONT PANEL (BEZEL REMOVED)



- Power On/Off button
- System Reset Button
- UID Button
- 5 LED Indicators:
 - Power LED
 - Hard drive activity LED
 - 2 x Network activity LEDs
 - System information (overheat/UID) LED
- 4x 3.5" Hot-swap Drive Bays

REAR PANEL



- Power Input Connect
- Multiple RJ45 Copper Emulation Ports as per model specification
- Multiple SFP+ Emulation Ports as per model specification
- 1 x RJ45 Copper Ethernet Port Management Port (MGMT)
- 2 x RJ45 Copper Ethernet Port
- 1 x UID LED Indicator
- 2 x USB 2.0 Ports
- 2 x USB 3.0 Ports
- 1 x VGA Display Port
- 1 x Serial Port

OPERATING SPECIFICATIONS

Input Rated: 100-240 VAC, 50/60 Hz, 7.5 Amp Max
 Operating Temperature Range: 0°C ~ 50°C
 Non-Operating Temperature Range: -40°C ~ 70°C
 Operating Relative Humidity Range (non-condensing): 8% ~ 90%
 PSU: 600W AC power supply w/ PFC (24-pin)

DIMENSIONS & WEIGHT

Unit		Gross (Packaged)	
Height:	43mm/1.7in	Height:	190mm/7.5in
Width:	437mm/17.2in	Width:	580mm/22.8in
Depth:	680mm/26.8in	Depth:	840mm/33.1in
Net Weight:	~11.4Kg/25.1lbs	Gross Weight:	~15.5Kg/34.2lbs

REGULATORY

- USA - UL listed, FCC
- Canada - CUL listed
- China - CCC Mark
- Europe/CE Mark
- EN 60950/IEC 60950-Compliant
- Germany - TUV Certified

WARRANTY

One (1) year from receipt, Return to Base.

A valid NE-ONE Service Agreement extends the warranty for the Service Agreement Term. NE-ONE Service also includes technical support, upgrades and certain enhancements.

NE-ONE ENTERPRISE MODELS

1 Gbps Model 2

- 2 x 1Gbps Emulation Ports
- 10 Network Objects
- 16 Soft Ports

1 Gbps Model 4

- 4 x 1Gbps Emulation Ports
- 20 Network Objects
- 32 Soft Ports

1 Gbps Model 6

- 6 x 1Gbps Emulation Ports
- 30 Network Objects
- 48 Soft Ports

1 Gbps Model 8

- 8 x 1Gbps Emulation Ports
- 40 Network Objects
- 64 Soft Ports

10 Gbps Model 2

- 2 x 10Gbps Emulation Ports
- 2 x 1Gbps Emulation Ports
- 20 Network Objects
- 64 Soft Ports

10 Gbps Model 4

- 4 x 10Gbps Emulation Ports
- 2 x 1Gbps Emulation Ports
- 40 Network Objects
- 128 Soft Ports

10 Gbps Model 6

- 6 x 10Gbps Emulation Ports
- 60 Network Objects
- 192 Soft Ports

PLEASE NOTE: The 10 Gbps Model 4 and Model 6 consists of different hardware. Please contact us for the technical specifications and for more information on 25 Gbps or 40 Gbps model options.